

ASDO SEEHAFENPOLLER – ASDO KPS 50 - 3000

Pollerkopf Trossenzug*		KPS 50 - 300	KPS 500 - 700	KPS 800 - 1000	KPS 1250 - 1500	KPS 2000	KPS 2500	KPS 3000
		50 - 300	500 - 700	800 - 1000	1250 - 1500	2000	2500	3000
Typ		KPS 1a	KPS 1a	KPS 1a	KPS 1b	KPS 2	KPS 2	KPS 3
a_p	[mm]	490	600	700	900	900	1050	1200
b_p	[mm]	490	600	700	820	900	1050	1200
h_k	[mm]	370	450	520	560	650	800	900
b_k	[mm]	400	490	580	650	760	820	960
t_k	[mm]	100	115	130	130	165	250	290
$\varnothing d_k$	[mm]	250	290	380	380	420	465	580
t_p	[mm]	80	95	120	120	150	160	210
A_r	[mm]	200	250	290	325	365	425	475
e_a	[mm]	90	100	125	340	320	350	420
e_b	[mm]	400	500	580	650	750	850	950
Gusswerkstoff:		EN-GJS-500 & G20Mn5+QT						
Verankerung		KPS 50 - 300	KPS 500 - 700	KPS 800 - 1000	KPS 1250 - 1500	KPS 2000	KPS 2500	KPS 3000
N_G / \varnothing_G		M27	M36	M56	M72	M72	M76	M90
m	[mm]	22	29	45	58	58	61	72
h_A	[mm]	120	160	220	255	255	290	355
h_M	[mm]	90	120	170	220	220	240	270
\varnothing_M	[mm]	40	60	90	105	105	115	140
h_T	[mm]	440	520	690	805	805	890	1065
h_G	[mm]	40	50	70	90	90	100	110
\varnothing_T	[mm]	85	110	170	210	210	230	270
h_V	[mm]	580	650	930	1100	1120	1340	1460
Stahlgüte:		ASDO-500						

*Trossenangriffswinkel nach EAU 2012

